8-Way RDM Enabled DMX Splitter

CE F© PROHS



09.218SP.04294

Important: Read All Instructions Prior to Installation

Function introduction

Female 12-24VDC power connector DMX/RDM outputs 5-8: DMX/RDM input feed through: (Requires male DC plug) 3/5 Pin female XLR connector 3/5 Pin female XLR connector Indicators for DMX/RDM outputs 1-8, all turn 8-Way RDM Enabled DMX Splitter on when DMX/RDM input 10 8**O**connected, all turn off 2 **(** 7 **O** when a fault of any of зΦ 6Ф the 8 outputs occurs 4 **(** 5 M DMX/RDM input indicator, turns on when DMX/RDM C€ ® RoHS 🗵 input connected Power indicator, turns on when power applied 12-24VDC power input: DMX/RDM outputs 1-4: DMX/RDM input: 2 groups Plug in type terminal 3/5 Pin female XLR connector 3/5 Pin male XLR connector


Product Data

No.	Input Voltage	Input Current	Input Signal	DMX/RDM Connection Ports	Connector Pin Out	Size(LxWxH)	Operation Temperature
1	12-24VDC	Max. 300mA	DMX/RDM	Input: (1x) Male 3-Pin XLR Output: (8x) Female 3-Pin XLR	Pin1: Ground Pin2: Data- Pin3: Data+	199x125x44mm	-20°C ~ +50°C
2	12-24VDC	Max. 300mA	DMX/RDM	Input: (1x) Male 5-Pin XLR Output: (8x) Female 5-Pin XLR	Pin1: Ground Pin2: Data- Pin3: Data+ Pin4: NC Pin5: NC	199x125x44mm	-20°C ~ +50°C

- 8-Way RDM enabled DMX splitter
- DMX/RDM compatible
- RDM enabled ANSI E1.20 compliant
- Extend both cable distance (up to 300m) and the number of devices (up to 32 devices per output, total 256 devices)
- Plug and play, 3/5-Pin XLR male DMX input, eight XLR female DMX outputs
- 8 outputs are full isolated from the input, the outputs are not isolated from each other
- Each output provides LED data indicators, providing full confirmation of proper operation
- Supports bi-directional communications for discovery, addressing and DMX control of RDM enabled devices
- A feed through XLR female connector is provided at the input, allowing this unit to be placed in the middle of an existing DMX chain

Safety & Warnings

- DO NOT install with power applied to device.
- DO NOT expose the device to moisture.



Note:

- 1) This splitter is placed in the middle of an existing DMX chain.
- 2) Max. allowed data cable length in a DMX chain is 300m, each output is branch DMX chain.
- 3) Max. allowed data cable length connected to each output (branch DMX chain) is 300m.
- 4) Max. 32 devices can be connected to each output of the splitter in daisy-chain.
- 5) Total 32*8=256 devices can be connected to 8 outputs of the splitter.
- 6) Please attach a 120ohm, 0.5W resistor between Data+ and Data- wires on the last device of each DMX chain.

Product Dimension

